IAPMO RESEARCH AND TESTING, INC.

5001 E. Philadelphia Street, Ontario, CA 91761 • Phone (909) 472-4100 • Fax (909) 472-4244 • www.iapmort.org







ERTIFICATE OF LISTING



IAPMO Research and Testing, Inc. is a product certification body which tests and inspects samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and warehouses as well as the assessment of the supplier's Quality Assurance System. This listing is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by Authorities Having Jurisdiction.

Issued To:

DALDORADO, LLC.

4327 ARNOLD AVE. NAPLES, FL 34104, United States

Product:

Suction Fittings

Products are in compliance with the following code(s): Uniform Swimming Pool, Spa and Hot Tub Code (USPC®) *Products are in compliance with the following standard(s)*

ANSI/APSP/ICC-16 2017

File Number: SP-10930 Revised Date: April 9, 2021

Effective Date: February 2019

Void After: February 2024*





Chief Technical Service Officer

*This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

This listing period is based upon the last date of the month indicated on the Effective Date and Void After Date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of the Product Certification Committee, or any evidence of non-compliance with applicable codes and standards or of inferior workmanship, may be deemed sufficient cause for revocation of this listing. Production of or reference to this form for advertising purposes may be made only by specific written permission of IAPMO Research and Testing, Inc. Any alteration of this certificate could be grounds for revocation of the listing. This document shall be reproduced in its entirety.

IAPMO RESEARCH AND TESTING, INC. CERTIFICATE OF LISTING



Issued To: DALDORADO, LLC. Effective Date: February 2019

File Number: SP-10930 Revised Date: April 9, 2021

Product: Suction Fittings Void After: February 2024

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Identification:

Fittings shall be permanently marked as follows in a manner so as to be visible after installation in the following sequence: (1)"VGBA ####", where #### indicates the year this standard was approved by the Americal National Standards Institute.

(2)maximum flow rate

(3)type of service, "Blockable" or "Unblockable" as appropriate.

(4)life of the fitting in years

(5)Cover/grates with only one set of flow ratings shall be marked "Wall ### GPM", and/or "Floor ### GPM", or "Wall/Floor ### GPM. Covers/grates with multiple sets of flow ratings shall be marked "For Flow Ratings See Instructions" or all flow ratings shall be marked on the cover/grate such that flow ratings are adjacent or otherwise associated with the SOFA model number.

(6)Manufacturers name, trade name, or requested trademark and

(7)a distinctive part number and

(8)model designation and the USPC certification mark®.

Characteristics:

Suction fittings for use in swimming pools, wading pools, spas, hot tubs, and other aquatic facilities.

Products listed on this certificate have been tested by an IAPMO R&T recognized laboratory. This recognition has been granted based upon the laboratory's compliance to the applicable requirements of ISO/IEC 17025.

IAPMO RESEARCH AND TESTING, INC. CERTIFICATE OF LISTING



Issued To: DALDORADO, LLC.

File Number: SP-10930

Product: Suction Fittings

Effective Date: February 2019

Revised Date: April 9, 2021

Void After: February 2024

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Models

Model Number	Description
DalMAX-SG-183624	Manufactured sump DalMAX-SO-183624, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 1984 GPM, Wall: 1440 GPM, Max Port Size = 8"
DalMAX-SG-183625	Manufactured sump DalMAX-SO-183625, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 1984 GPM, Wall: 1440 GPM, Max Port Size = 8"
DalMAX-SG-183628	Manufactured sump DalMAX-SO-183628, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2480 GPM, Wall: 1909 GPM, Max Port Size = 10"
DalMAX-SG-183634	Manufactured sump DalMAX-SO-183634, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2869 GPM, Wall: 2080 GPM, Max Port Size = 12"
DalMAX-SG-185424	Manufactured sump DalMAX-SO-185424, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2872 GPM, Wall: 2872 GPM, Max Port Size = 10"
DalMAX-SG-185427	Manufactured sump DalMAX-SO-185427, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2872 GPM, Wall: 2872 GPM, Max Port Size = 10"
DalMAX-SG-185428	Manufactured sump DalMAX-SO-185428, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2944 GPM, Wall: 2872 GPM, Max Port Size = 12"
DalMAX-SG-185429	Manufactured sump DalMAX-SO-185429, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 2944 GPM, Wall: 2872 GPM, Max Port Size = 12"
DalMAX-SG-185434	Manufactured sump DalMAX-SO-185434, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-SG fasteners, Floor: 4412 GPM, Wall: N/A, Max Port Size = 14"
DalMAX-SG-242430	Manufactured sump DalMAX-SO-242430, one (1) DalMAX-GO-2424 grate model with DFS-DalMAX-SG fasteners, Floor: 1734 GPM, Wall: 1600 GPM, Max Port Size = 10"
DalMAX-SG-242412-03	Manufactured sump DalMAX-SO-242412, one (1) DalMAX-GO-2424 grate model with DFS-DalMAX-SG fasteners, Floor: 408 GPM, Wall: N/A, Max Port Size = 3"
DalMAX-SG-242412-04	Manufactured sump DalMAX-SO-242412, one (1) DalMAX-GO-2424 grate model with DFS-DalMAX-SG fasteners, Floor: 712 GPM, Wall: N/A, Max Port Size = 4"
DalMAX-SG-242412-06	Manufactured sump DalMAX-SO-242412, one (1) DalMAX-GO-2424 grate model with DFS-DalMAX-SG fasteners, Floor: 1664 GPM, Wall: N/A, Max Port Size = 6"
DalMAX-FG-183624	Retrofit frame DalMAX-FO-1836, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 1984 GPM, Wall: 1440 GPM, Max Port Size = 8"
DalMAX-FG-183625	Retrofit frame DalMAX-FO-1836, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 1984 GPM, Wall: 1440 GPM, Max Port Size = 8"
DalMAX-FG-183628	Retrofit frame DalMAX-FO-1836, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2480, Wall: 1909, Max Port Size = 10"

IAPMO RESEARCH AND TESTING, INC. CERTIFICATE OF LISTING



Issued To: DALDORADO, LLC.

File Number: SP-10930

Product: Suction Fittings

Effective Date: February 2019

Revised Date: April 9, 2021

Void After: February 2024

This certificate is not evidence of current listing. To verify listing status, visit the IAPMO R&T Product Listing Directory at pld.iapmo.org

Model Number	Description
DalMAX-FG-183634	Retrofit frame DalMAX-FO-1836, two (2) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2869 GPM, Wall: 2080 GPM, Max Port Size = 12"
DalMAX-FG-185424	Retrofit frame DalMAX-FO-1854, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2872 GPM, Wall: 2872 GPM, Max Port Size = 10"
DalMAX-FG-185427	Retrofit frame DalMAX-FO-1854, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2872 GPM, Wall: 2872 GPM, Max Port Size = 10"
DalMAX-FG-185428	Retrofit frame DalMAX-FO-1854, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2944 GPM, Wall: 2872 GPM, Max Port Size = 12"
DalMAX-FG-185429	Retrofit frame DalMAX-FO-1854, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 2944 GPM, Wall: 2872 GPM, Max Port Size = 12"
DalMAX-FG-185434	Retrofit frame DalMAX-FO-1854, three (3) DalMAX-GO-1818 grate model with DFS-DalMAX-FG fasteners, Floor: 4412 GPM, Wall: N/A, Max Port Size = 14"
DalMAX-FG-242430	Retrofit frame DalMAX-FO-2424, one (1) DalMAX-GO-2424 grate model with DFS-DalMAX-FG fasteners, Floor: 1734 GPM, Wall: 1600 GPM, Max Port Size = 10"
DMD-FG-2424	Retrofit frame DalMAX-FO-2424, one (1) DMD-GO-2424 grate model with DFS-FASTSET-MD-CU fasteners, Floor: 825 GPM, Wall: 825 GPM, Max Port Size = 8"